



**AIR DRYER SPECIFICATIONS**

Air Handling Capacity, m <sup>3</sup> /hr (CFM) Nm <sup>3</sup> /min	-	5097 (3000) 85 - Continuous Flow
Maximum Working Pressure, psi (bar) MPa	-	435 (30) 3.0
Maximum Dew Point Range	-	-70°C
Outlet Dew point Meter	-	Mitchell EA-TX-100 Inlet / Outlet
Flange Size	-	3", 300#, RF Flange
Air Handling Hoses, psi (bar)	-	2", 600 (41.3), FJICHT -40 - +150 dc
Oil Mist Separator	-	0.1 & 0.01 um Sieves
Ex Approved Panel	-	BET56-C
Skid Framing, mm	-	2510 x 2710 x 2896 x 5MT
No of Units	-	2



**AIR COOLER SPECIFICATIONS**

Air Handling Capacity, m <sup>3</sup> /hr (CFM) Nm <sup>3</sup> /min	-	5097 (3000) 85 - Continuous Flow
Maximum Working Pressure, psi (bar) MPa	-	435 (30) 3.0
Aftercooler Performance	-	Reduction of Temperature from 80°C to 40°C
Power Requirements	-	220VAC, 50Hz
Inlet / Outlet Flange Size	-	6", 300#, RF Flange
Air Handling Hoses, psi (bar)	-	2", 600 (41.3), FJICHT -40 - +150 degree Celsius
Ex Approved Panel	-	BET56-C
Skid Framing, mm	-	3100 x 1700 x 2500 x 3MT
No of Units	-	2